


MIMIK 20 CP/T2 EM3P




| | |
|----------------------------------|---------------------------------------|
| Part number | 304397 |
| Lampholder: | LED |
| Light Source: | LED |
| Wattage: | 21 W |
| Finish: | AN-96 / Anthracite gray / Textured |
| Insulation class: | I |
| Degree of protection: | IP65 |
| IK-J-xxIP: | IK06 1J xx3 |
| CRI: | 70 |
| Kelvin: | 4000 |
| Power factor / COS Φ: | >0.9 |
| Optic: | Pedestrian and cycle reflector type 2 |
| Lightsource lumen output: | 2453 lm |
| Luminaire lumen output: | 2005 lm |
| L: | L80 |
| B: | B10 |
| Lifetime: | 60000 h |
| Ta MIN luminaire (°C): | 0 |
| Ta MAX luminaire (°C): | 25 |
| ULR: | 0% |




Description

- Wall-mounted LED luminaire, comprising:
- Die-cast aluminium housing, powder-polyester coated ISO 9227
 - Transparent, tempered, flat glass diffuser, screen-printed inside for the MIMIK versions
 - Anti-ageing silicone gasket
 - Built-in driver
 - MIMIK luminaires are equipped with high-transmittance polycarbonate lenses with different light distributions to meet the most diverse lighting requirements
 - EM/3P version is designed for multipurpose and 3 hours sustained emergency lighting
 - 3 hours
 - M versions, i.e. single emission, are supplied with a single light source and are designed to allow a single sided light output either upwards or downwards
 - "CP" versions feature asymmetric light distribution suitable for bicycle and pedestrian pathways
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



OPTIONAL ACCESSORIES

MIMIK CP/T2 - CP/T3 - A60/W



310445

Customising ring / Facade Accessory

Anthracite gray
