



## Features

- External Duct Grade
- Supports Gigabit Ethernet
- Fast feed box
- Sequential metre markings (305-0)
- CPR compliant to Fca

## Product Overview

Excel Category 5e Unscreened External Grade Cables are manufactured and tested to the ISO 11801, EN 50173 and ANSI/TIA-568-C standards for enhanced performance Category 5 cables. Each cable consists of 8 colour coded polyethylene insulated conductors. These are twisted together to form 4 pairs with varying lay lengths. These pairs are jacketed in a heat and UV, moisture resistant black polyethylene outer sheath, making this cable ideal for outdoor installation.

Features	
1: Category	5E
2: Total number of cores	8
3: Stranding element	Pairs
4: Outer sheath material	PE
5: Low smoke (acc. EN 61034-2)	no
6: Halogen free (acc. EN 60754-1/2)	no
7: Overall screening	None
8: Conductor screening	None
9: Outer sheath colour	Black
10: Conductor category	Class 1 = solid
11: AWG-size	24
12: Number of strands	1
13: Conductor material	Cu, bare
14: Core insulation	Solid PE
15: Core identification	Colour

## Features

16: Outer diameter approx.	5.2 mm
17: NVP value	70 %
18: Operating Temperature Range	-20...60 °C