



## DOWNUNDER PUR 155

recessed fitting, LED, 3000K, square, white, L/W/H 12/3.2/15.5 cm, incl. leaf springs

Article number	151952
Feed-in capability	No
Lamp included	No
Installation length	14 cm
Installation width	10.5 cm
Installation depth	3.5 cm
Width	12 cm
Height	15.5 cm
Depth	3.2 cm
Net weight	0.264 kg
Gross weight	0.342 kg
Voltage	500 Volts
Protection class	III
Material	Aluminium/steel
Colour	white
Way of mounting	Recessed wall mounting
Remark 1	Operate with suitable 480mA drivers only
Average lifespan	30000 Hours
Colour temperature	3000 Kelvin
Colour rendering index	80
Luminous flux	380 lm
Energy efficiency class	A++
fastCalcEnabled	No
ranking	300
Catalogue page	BIG WHITE 2018: 577
Light distribution type 1	Direct

Aluminium recessed wall light of our DOWNUNDER LED series. The not visibly mounted LED emits the light indirectly onto the surface to be illuminated. This guarantees glare-free illumination of walkways and much more. The DOWNUNDER PUR 120 recessed fitting is available in white colour version. To operate the recessed fitting, a suitable LED driver is required providing 480mA. A mounting frame for installation in masonry can be ordered from the accessory. This luminaire contains built-in LED lamps. EEI: A - A++. The lamps in the luminaire cannot be replaced.

