

ENSTO

BETA7-BT-EP

Panel heater

| | |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code | BETA7-BT-EP |
| GTIN | 6438100339487 |
| Name | Panel heater Beta |
| Description | Beta convector 750W/230V with electronic thermostat and connection plug for fixed installation. White color, RAL9010. IP21. 389x719mm. |
| Description | Ecodesign-compatible convector with accurate electronic thermostat, which can be controlled from the thermostat or with downloadable Bluetooth-application (Android and iOS). Features for temperature control are calendar, boost, and vacation. Energy consumption can easily be monitored from the app. Thermostat has a wireless slave-heater feature with a maximum of 10 convectors. |
| Vendor | Ensto Finland Oy |



Technical specification

Basic

Thermostat: EPHE5-BT

Colors

Color: White

Others

ETIM Class: EC000523

Ratings

Degree of protection: IP21
 Power: 750 W
 Protection class: II
 Rated frequency: 50 Hz
 Rated voltage: 230 ... 230 V

Dimensions

| | |
|-----------------------|-------------------|
| Dimensions l x w x h: | 56 x 720 x 390 mm |
| Net Weight: | 3.93 kg |
| Weight: | 3.93 kg |

ETIM 7

Etim

| | |
|-----------------------------------|-------------|
| Adaptive (self-learning): | True |
| Air exhaust: | Front side |
| Colour: | White |
| Connected load: | ≥ 750 |
| Consumption indication: | True |
| Degree of protection (IP): | IP21 |
| Depth: | 56 mm |
| Digital indication: | False |
| Electro-connection: | 1/N~230 V |
| Frost protection circuit: | True |
| Height: | 390 mm |
| Model: | Other |
| Mounting method: | Wall model |
| Open window detection: | False |
| Operation by app: | True |
| Overheating protection: | True |
| Position control panel: | Side |
| Programmable with remote control: | True |
| Protection class: | II |
| Suitable for bus connection: | False |
| Temperature adjustment: | 5 ... 30 °C |
| Type of regulation: | Electronic |
| Weight: | 3.93 kg |
| Width: | 720 mm |
| With fan: | False |
| With presence indicator: | False |
| With timer: | True |

Packaging

Pallet package

| | |
|---------------|---------|
| Unit: | pcs |
| Package size: | 30 |
| Depth: | 1200 mm |
| Width: | 800 mm |
| Height: | 1000 mm |

Default package

| | |
|----------------------|-------------|
| Unit: | PCE |
| Package size: | 1 |
| Depth: | 747 mm |
| Width: | 404 mm |
| Height: | 94 mm |
| Weight: | 4.519 kg |
| Volume: | 28.368072 l |