

PratiKa socket - black - 2P + E - 10/16 A - 250 V - French - IP54 - flush - back

PKN61N

Range	PratiKa
Product or component type	Socket-outlet
Device short name	PratiKa socket
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	French

#### Complementary

Complementary	
[In] rated current	16 A 10 A
Network frequency	50/60 Hz
[Ue] rated operational voltage	250 V
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Pins: stainless steel Springs: stainless steel
Cover type	Lid
Device mounting	Flush
Mounting mode	Panel-mounted
Connections - terminals	Captive screws
Location of conductor inlet	Back
Net weight	0.05 kg
Base dimension	65 x 85 mm
Height	85 mm
Width	65 mm
Depth	45.2 mm
Colour	Black (RAL 7016)

### **Environment**

Standards	IEC 60309-2
	IEC 60309-1

IP degree of protection	IP54 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 62262
Fire resistance	850 °C conforming to IEC 60695-2-11
Relative humidity	50 % at 40 °C
<b>-</b>	70 % at 30 °C
	90 % at 20 °C
Ambient air temperature for	35 °C ( 86400 s )
operation	-2540 °C

# **Packing Units**

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	50.0 g
Package 1 Height	4.3 cm
Package 1 width	6.5 cm
Package 1 Length	8.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	20
Package 2 Weight	1.1 kg
Package 2 Height	9 cm
Package 2 width	27 cm
Package 2 Length	22 cm
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Weight	3.787 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

### **Contractual warranty**

Warranty 18 months
--------------------