



Ledinaire Waterproof Tube Housing

WT050C 2xTLED L1500

220 to 240 V - 50 or 60 Hz - Safety class II - - - Dust penetration-protected, jet-proof - 5 J vandal-protected - White

The Ledinaire range contains a selection of popular off-the-shelf LED luminaires that comes with the high Philips quality levels at a competitive price. Reliable, energy efficient and affordable – just what you need.

Product data


General Information	
Protection class IEC	Safety class II
CE mark	CE mark
Material	Polycarbonate
Angle	-
Accessory color	White

Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz

Mechanical and Housing	
Overall length	1580 mm
Overall width	95 mm
Overall height	84 mm
Dimensions (Height x Width x Depth)	84 x 95 x 1580 mm (3.3 x 3.7 x 62.2 in)

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]


Product Data	
Full product code	871016336605099
Order product name	WT050C 2xTLED L1500
EAN/UPC - Product	8710163366050
Order code	911401807681
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	9
Material Nr. (12NC)	911401807681
Net Weight (Piece)	1.190 kg



Ledinaire Waterproof Tube Housing

Dimensional drawing

WT050C L1500 2 Tube



Ledinaire Waterproof Tube Housing

