

EOS NOCUT WINTER VV913



HIGH PERFORMANCE POLYETHYLENE KNITTED GLOVE - DOUBLE NITRILE-COATING PALM

Model VV913JA08



Product specifications

High performance polyethylene support. TPR reinforcement on back and fingertips. Double smooth nitrile coating/foam nitrile on palm and fingertips. Embossed inside reinforcement on palm. Inside acrylic lining. Kevlar® thread on all the seams.

Support: High performance Polyethylene fibres.

Coating: nitrile.

Back reinforcement: TPR.

Reinforcement on thumb/forefinger: TPR.

Lining: Acrylic.

COLOUR

Yellow-Grey-Black

SIZE

08

Product Features and Benefits

0%
SILICONE
DMF



Double nitrile coating for oily work

1st smooth nitrile coating : impermeable to oils
2nd nitrile foam coating : good adhesion



Flexible reinforcements

Increased protection from impacts and pinches



Reinforcement between the thumb and index finger and on the palm

Increased protection



Acrylic interior support

Excellent comfort all day long
Maintains heat



Protection against impact in the metacarpal area. After an energy impact of 5J, the force transmitted to the back of the hand cannot exceed 4 kN.



Available only with header card

Very good resistance to abrasion and cutting

Increased lifespan

Kevlar® thread stitching

Increased lifespan

8 cm cuff with Velcro closure

Perfect adjustment
Reduced discomfort at the wrist, during prolonged use



Cut level D

Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements
5: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

- 4: Resistance to abrasion (from 1 to 4)
- X: Resistance to cutting (from 1 to 5)
- 4: Resistance to tear (from 1 to 4)
- 4: Resistance to puncture (1 to 4)
- D: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)
- P: Protection against impact in metacarpal area (P) (EN13594:2002 6.8.2)



EN511:2006 Protective gloves against cold (X = Unrealized test)

- 1: Resistance to convective cold (from 1 to 4)
- 3: Resistance to contact cold (from 1 to 4)
- X: Waterproof (0 or 1)



USA STANDARDS

ANSI-ISEA 105:2016 Hand protection

- A4: Resistance to cutting by sharp objects (from A1 to A9)



Item details

Item details	Bar code	COLOUR	SIZE
VV913JA08	3295249233051	Yellow-Grey-Black	08