


PCE data sheet

article#	234-9
article description	CEE-connector 63A 4p 9h IP67 POWER TWIST
description long	CEE-connector 63A 4p 9h IP67 POWER TWIST housing material: PA6 rated current: 63A number of poles: 4 (3P+PE) clock-position: 9h rated voltage/frequency: 200-250V~ / 50+60Hz contacts: brass, with lamellar spring (CuBe) connection technology: frame terminals with screws IP protection class: IP66/IP67
GTIN (EAN)	9003399047442
country of origin	AT
customs number	85366990
net weight	0.710 kg
packaging quantity	2
minimum order quantity	2

ETIM 8.0	EC001320
IEC-amperage	63 A
Number of poles	4
Voltage according to EN 60309-2	200 - 250 V (50+60 Hz) blue
Clock hour position	9 h
Identification colour	Blue
RAL-number	7046
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Angle of plug	Straight
Cable entry	Gland nut
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Untreated

a	269 mm
b	114 mm
K (cable Ø)	14,5-36 mm
SW	61 mm
wire flexible	6-16 mm ²
contact screws	200 Ncm
strain relief	1500 Ncm
dismantling length	100 mm
stripping length	15-18 mm



<https://www.pcelectric.at/shop/en/?func=detail&artnr=234-9>



www.manufacturer-safety.info