



 Illustrative photo

XREEL250 extension cord - 4xGS output with ter.

Product No

92501T48273

[See variants](#)

XREEL250 extension cord - 4xGS output with ter.

**Housing material :** Plastic

**Type of cable used :** H05RR-F

**Cable cross section :** 2.5 mm<sup>2</sup>

**Number of cores :** 3

**Number of CEE sockets :** 0

**Number of sockets with protective contact (type F) :** 4

**Number of Bipasso sockets (Italy) :** 0

**Number Type 13 (Swiss) sockets :** 0

**Number of Type 15 (Swiss) sockets :** 0

**Number of Type 23 (Swiss) sockets :** 0

**Number of Type 25 (Swiss) sockets :** 0

**Cord length :** 40 m

**With stand :** Yes

**Automatic cord rewind :** No

**With thermal protection :** Yes

**Degree of protection (IP) :** IP20



Housing material	Plastic	Cord length	40 m
Type of cable used	H05RR-F	With stand	Yes
Conductor cross-section	2.5mm <sup>2</sup>	Automatic cord rewind	NO
Number of veins	3	With thermal protection	Yes
Number of protective contact sockets (type F)	4	Degree of protection (IP)	IP20

PCE POLSKA SP. Z O.O. | st. Podwalna 8a | 58-200 Dzierżonów | Tel. 74 831 76 00 | [pce@pce.pl](mailto:pce@pce.pl)