

PRODUCT-DETAILS

CL-523R

PILOT LIGHT CL-523R 230V a.c.



General Information

| | |
|-----------------------|------------------------------------------------------------------------------------|
| Extended Product Type | CL-523R |
| Product ID | 1SFA619402R5231 |
| EAN | 7320500250488 |
| Catalog Description | PILOT LIGHT CL-523R 230V a.c. |
| Long Description | Compact Pilot Light - Pilot light head - Red - Illuminated - Lamptype: LED 230V AC |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number | 85369001 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SFC151003C0201 |
| Instructions and Manuals | 1SFC151003C0201 |

Dimensions

| | |
|--------------------|--------|
| Product Net Width | 0.03 m |
| Product Net Height | 0.03 m |

| | |
|----------------------------|----------|
| Product Net Depth / Length | 0.055 m |
| Product Net Weight | 0.022 kg |

Technical

| | |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient Air Temperature | Operation -25 ... +70 °C Storage -30 ... +85 °C |
| Color | Red |
| Actuator Type | Pilot light head |
| Illumination | Illuminated |
| Lamp Type | LED 230V AC |
| Degree of Protection | Front IP66 Front IP67 Front IP69K Terminals IP20 |
| Enclosure Type NEMA | Type1 Type12 Type13 Type3R Type4 Type4X |
| Pollution Degree | 3 |
| Rated Frequency (f) | Supply Circuit 50 / 60 Hz |
| Rated Operational Voltage | 230 V AC |
| Connecting Capacity | Flexible with Ferrule 1 x 0.75...2.5 mm ² Flexible with Ferrule 2 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 1 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 2 x 0.75...2.5 mm ² Flexible 1 x 0.75 ... 2.5 mm ² Flexible 2 x 0.75 ... 2.5 mm ² Solid 1 x 0.75...2.5 mm ² Solid 2 x 0.75...2.5 mm ² |
| Connection Type | Screw Clamp |
| Terminal Type | Screw Terminals |
| Tightening Torque | 0.9 N·m Control Circuit 0.9 N·m |
| Wire Stripping Length | 8 mm Control Circuit 8 mm |

Technical UL/CSA

| | |
|---------------------|----------------|
| Connecting Capacity | 1x 18...14 AWG |
| UL/CSA | 2x 18...14 AWG |

Environmental

| | |
|------------------|-----------------------------------------------------------------|
| RoHS Status | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
| RoHS Date | 0626 5 |
| RoHS Information | 1SFC151012D0202 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Business |

Certificates and Declarations

| | |
|-----------------|---------------------|
| CB Certificate | CQC_CN_CN50749 |
| CQC Certificate | CQC2003010305054693 |
| Declaration of | 2020980305001187 |

Conformity - CCC

Declaration of

1SFA1-70

Conformity - CE

Container Information

| | |
|--------------------------------|--------------|
| Package Level 1 Units | bag 10 piece |
| Package Level 1 Width | 0.1 m |
| Package Level 1 Depth / Length | 0.1 m |
| Package Level 1 Height | 0.03 m |
| Package Level 1 Gross Weight | 0.022 kg |

Classifications

| | |
|----------------------------|-------------------------------------|
| Object Classification Code | E |
| ETIM 7 | EC000272 - Indicator light complete |
| ETIM 8 | EC000272 - Indicator light complete |
| eClass | V11.0 : 27371223 |
| UNSPSC | 39121500 |
| E-Number (Sweden) | 3711390 |

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CL Compact Pilot Lights

