

PRODUCT-DETAILS

# OT63F3C

## OT63F3C CHANGE-OVER SWITCH



### General Information

Extended Product Type	OT63F3C
Product ID	1SCA105338R1001
EAN	6417019392974
Catalog Description	OT63F3C CHANGE-OVER SWITCH
Long Description	63A Manual Change-Over Switch, Handle and shaft need to be ordered separately, Open transition

### Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

## Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301067M0208

## Dimensions

Product Net Width	105 mm
Product Net Height	92 mm
Product Net Depth / Length	85 mm
Product Net Weight	0.64 kg

## Technical

Rated Operational Current AC-21A ( $I_g$ )	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A
Rated Operational Current AC-22A ( $I_g$ )	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A ( $I_g$ )	(380 ... 415 V) 45 A (500 V) 45 A (690 V) 20 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 22 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	$\Theta = 40 \text{ }^\circ\text{C}$ 63 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 63 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	750 V
Rated Operational Voltage	750 V
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 1 kiloampere rms
Power Loss	2.8 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft not included
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Standards	UL 98 / IEC60947-3
Mounting Type	Base mounting
Number of Poles	3
Cable Cross-Section	1.5 ... 35 mm <sup>2</sup>
Degree of Protection	Front IP20
Transition Type	Open

---

**Technical UL/CSA**


---

Ampere Rating	63 A
Horsepower Rating UL/CSA	(acc. to UL 200 V) 15 Hp (acc. to UL 208 V) 15 Hp (acc. to UL 240 V) 15 Hp (acc. to UL 480 V) 30 Hp (acc. to UL 600 V) 30 Hp

---



---

**Environmental**


---

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

---



---

**Certificates and Declarations**


---

Declaration of Conformity - CE	1SCC303020D2702
REACH Declaration	1SCC011021D0201

---



---

**Container Information**


---

Package Level 1 Units	1 piece
Package Level 1 Width	102 mm
Package Level 1 Depth / Length	205 mm
Package Level 1 Height	103 mm
Package Level 1 Gross Weight	0.64 kg
Package Level 1 EAN	6417019392974

---



---

**Classifications**


---

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601450
E-Number (Sweden)	3171263

---



---

**Categories**


---

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

