

STARTERKIT WCU 650

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com



With the fully encapsulated WCU 501 and WCU 650 logic modules, you monitor, control and regulate your processes - even under extreme environmental conditions. In this regard, the WCU series offers optimum dimensions, performance, robustness and user-friendliness. The graphic and intuitive Micon-L programming environment enables flexible switching of the analogue and digital inputs, plus the digital outputs too. The scope of both the software and the hardware can be expanded to suit customer requirements upon request. .

General ordering data

| | |
|------------|---|
| Version | graphically programmable logic module incl. programming adapter, CAN interface, Mounting foot |
| Order No. | 2007290000 |
| Type | STARTERKIT WCU 650 |
| GTIN (EAN) | 4050118392517 |
| Qty. | 1 pc(s). |

Creation date October 26, 2023 5:52:28 PM CEST

Catalogue status 14.10.2023 / We reserve the right to make technical changes.

STARTERKIT WCU 650

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|-------|-----------------|------------|
| Depth | 30 mm | Depth (inches) | 1.181 inch |
| Height | 93 mm | Height (inches) | 3.661 inch |
| Width | 45 mm | Width (inches) | 1.772 inch |
| Net weight | 178 g | | |

Temperatures

| | | | |
|-----------------------------|-----------------------|-----------------------------|----------------|
| Storage temperature | -40 °C...70 °C | Operating temperature | -40 °C...70 °C |
| Operating temperature, min. | -40 °C | Operating temperature, max. | 70 °C |
| Humidity | 5 - 95% rel. humidity | | |

Connection data

| | |
|--------------------|---|
| Type of connection | Plug-in spring-type terminals (0.25 - 1.5 mm ²) |
|--------------------|---|

General data

| | |
|----------------------|--|
| Vibration resistance | min. 50 m/s ² (5 g) @ 10...150 Hz |
|----------------------|--|

Power supply

| | |
|-----------------------------|-----------------------------------|
| Reverse polarity protection | yes (combined with external fuse) |
|-----------------------------|-----------------------------------|

System data

| | |
|-----------|---------|
| Interface | TTL 232 |
|-----------|---------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC001417 | ETIM 7.0 | EC001417 |
| ETIM 8.0 | EC001417 | ETIM 9.0 | EC001417 |
| ECLASS 9.0 | 27-24-22-16 | ECLASS 9.1 | 27-24-22-16 |
| ECLASS 10.0 | 27-24-22-16 | ECLASS 11.0 | 27-24-22-16 |
| ECLASS 12.0 | 27-24-22-16 | ECLASS 13.0 | 27242216 |

Approvals

Approvals



| | |
|-------------------------|------------|
| ROHS | Conform |
| UL File Number Search | UL Website |
| Certificate no. (cULus) | E141197 |

STARTERKIT WCU 650

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data**Downloads**

| | |
|--------------------|---|
| Engineering Data | CAD data – STEP |
| Software | Runtime Software – Programmiersoftware miCon-L |
| User Documentation | Handbuch WCU-Serie Deutsch Manual WCU-Series English |
| Catalogues | Catalogues in PDF-format |

STARTERKIT WCU 650

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

Drawings

www.weidmueller.com

