

**CBC-SP 12-100/25 V2 WT****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Similar to illustration**

Spiral and webbing hoses are particularly suitable for the construction of space-saving cable routing systems in switch gears and control cabinets. They are used for guiding, protecting and bundling cables and wires - for example, in the transition between the enclosure interior and the door.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Version    | Protective cable hose coil |
| Order No.  | <a href="#">2588640000</a> |
| Type       | CBC-SP 12-100/25 V2 WT     |
| GTIN (EAN) | 4050118602500              |
| Qty.       | 25 m                       |

## CBC-SP 12-100/25 V2 WT

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Dimensions and weights

|          |            |                 |            |
|----------|------------|-----------------|------------|
| Length   | 100,000 mm | Length (inches) | 3,937 inch |
| Diameter | 10 mm      | Net weight      | 23.2 g     |

### Temperatures

|                             |             |                             |        |
|-----------------------------|-------------|-----------------------------|--------|
| Operating temperature range | -15...60 °C | Operating temperature, min. | -15 °C |
| Operating temperature, max. | 60 °C       |                             |        |

### General information

|                             |                       |                           |        |
|-----------------------------|-----------------------|---------------------------|--------|
| Bundle diameter, max.       | 100 mm                | Bundle diameter, min.     | 12 mm  |
| Colour                      | white                 | Diameter                  | 10 mm  |
| Material                    | Polyethylene          | Nominal diameter          | 7.6 mm |
| Operating temperature range | -15...60 °C           | UL 94 flammability rating | V-2    |
| Usable cross-section        | 7,853 mm <sup>2</sup> |                           |        |

### Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001182    | ETIM 7.0    | EC001182    |
| ETIM 8.0    | EC001182    | ETIM 9.0    | EC001182    |
| ECLASS 9.1  | 27-43-03-03 | ECLASS 10.0 | 27-43-03-03 |
| ECLASS 11.0 | 27-43-03-03 | ECLASS 12.0 | 27-43-03-03 |
| ECLASS 13.0 | 27430303    |             |             |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|            |  |
|------------|--|
| Catalogues | <a href="#">Catalogues in PDF-format</a> |
|------------|--|